SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

- 1610 E. Ball Road, Anaheim, California 92805 SOUTHERN ZONE

Operation under this permit must be conducted in compliance with all information included with the initial application and the initial permit conditions. The equipment must be properly maintained and kept in good operating condition at all times. In accordance with Rule 206. this Permit to Operate or copy must be posted on or within 8 meters of equipment. 

LEGAL OWNER OR OPERATOR: THE ARNOLD ENGINEERING COMPANY

. E: APPL. NO. 03527A

-- 1

: E.A

7 4

1 12 3

**EQUIPMENT** LOCATED AT:

1551 EAST ORANGETHORPE AVENUE, FULLERION, CALIFORNIA

**SEMS-RM DOCID # 1192020** 

EQUIPMENT DESCRIPTION AND CONDITIONS:

SPRAY BOOTH, CUSTOM, BENCH DRY FILTER TYPE, 7'-3" W. x 4'-9" H. x 2'-6" D., WITH ONE 1/2 H.P. EXHAUST FAN AND FOUR EXHAUST FILTERS, EACH 16" x 25" x 2".

## CONDITIONS:

- THIS SPRAY BOOTH MUST NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE FILTERING MEDIA.
- BE USED TO THIN, REDUCE OR DILUTE PHOTOCHEMICALLY REACTIVE SOLVENT MUST NOT COATING MATERIALS USED IN THIS EQUIPMENT.

. (CONTINUED OF PAGE 2)

or an earlier date if equipment is moved, altered, or changes This initial permit must be renewed by This initial permit must be renewed by JANIARY 26, 1980 — or an earlier date if equipment is moved, altered, or ownership. If billing for annual renewal fee (Rule 301.1) not received by expiration date, contact Zone office above.

This permit does not authorize the emission of air contaminants in xcess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules of the Air Quality Management District. This permit cannot be considered as permission to violate existing laws, ordinances, regulations or statutes of other government agencies.

SCAQM3 001

3750Da 526R

**VOID UNLESS VALIDATED** mn

AIR POLLUTION CONTROL OFFICER

BY DATE 1/26/79

~ 76P235s. 2/77

CONTINUATION OF PERMIT NO (MUST BE DISPLAYED WITH PERMIT)

S 02801

3. THE TOTAL QUANTITY OF COATINGS AND SOLVENTS USED IN THIS EQUIPMENT MUST NOT EXCEED 0.8 GALLON IN ANY ONE DAY OR 0.2 GALLON IN ANY ONE HOUR.

APPL. NO. 03527A

1000

Page 2 of 2 Pages

16-500191 Rev 2/77